SNMP settings

Successfully pass the free certification exam at IW Academy and become an Infinet Certified Engineer.

To the certification exam

SNMP allows the administrator to gather information about key device parameters and wireless links, including information about changes. The use of any monitoring system helps to timely receive information about the network infrastructure state using Infinet devices. Currently, the devices family supports SNMP protocol versions v1 v2c and v3.

The SNMP Protocol has two branches, the agent and the management stations:

- The agent sends data to the management station. Monitoring system provides data gathering from all agents in the network.
- The monitoring system receives and processes events.
- The information is passed through requests and replies with the use of the MIB.
- The management station or monitoring system is responsible for decoding the SNMP packets and providing an interface to the administrator.

General settings

This section allow to enable/disable SNMP protocol support.

General settings Enabled: Contact person: Max Mad Location: 55.75, 37.6167

Figure - General SNMP settings		
Parameter	Description	
Enabled	Enable/disable the SNMP service in the device.	
Contact person	A reference information about the device owner.	
Location	The geographical location where the unit is installed, used as a reference information about the physical device's location.	

SNMP v1/v2c SNMP v1/v2c

Enabled (read only):
Community:
public

Figure - SNMP v1/v2c configuration

Parameter	Description
Enabled	Enable/disable the SNMP v.1 and v.2c support. The first version of the SNMP protocol lacks security, that hinders its use for network management, so SNMP v.1 and v.2c operates in read-only mode. Enabled by default.
Community	Set the community name for read-only mode of SNMP v.1 and v.2c, by default: " <i>public</i> ". The community name passes along with the data packet in clear text.

SNMP v3

Due to the security level of SNMP v.3 is higher than of SNMP v.1 and v.2c, it allows not only the data collection but also to manage devices. Detailed information about the devices management via the monitoring system is available in the corresponding article.

SNMP v3

User Name	Password	Security	Readonly	Admin	Privacy Password	Privacy Protocol		
admin	masterkey	Auth / No privacy	No	Yes	-	DES	/	×
root	root1234	Auth / No privacy	No	Yes	-	DES	/	×
			+ Add	SNMP v3 User				

Figure SNMP v3 configuration

To add an SNMP v3 user, click the corresponding button and fill in the following fields:

Parameter	Description			
User name	SNMP v3 user name.			
Password	SNMP v3 password.			
Security	Security level:			
	 "No auth / No privacy" – the lowest security level without authentication and privacy, only Username needs to be set. This level of protection does not allow management via the monitoring system. "Auth / No privacy" – middle level with authentication but without privacy, Username and Password are required. "Auth / Privacy" – highest level with authentication and privacy, Username, Password, Privacy Password and Privacy Protocol should be set. 			
Readonly	Enable/disable the read-only mode, readonly is set by defaut.			
Admin	Enable/disable the full access to all parameters, for example, the ability to reboot the device. By default an access is limited.			
Privacy password	Set the privacy password, it is necessary when privacy is enabled for the required security level.			

Edit SNMP v3 User	
User Name:	
admin1	
Password:	
admin1122	
Security:	
Auth / No privacy	
Readonly:	
Admin:	С
Privacy Password:	
Privacy Protocol:	
des	
Close	

SNMP traps

The devices polling cycle of the monitoring system is 5 minutes. To speed up the process of detecting incidents on devices, SNMP traps can be send each time an incident occurs, regardless of the polling process.

Title

SNMP Traps					
Enable SNMF	Enable SNMP Traps:				
Source IP add	ddress: 192.168.103.11				
Destination address Port					
192.168.200.5	192.168.200.55 : 162				
+ Add SNMP Trap					
Figure - SNMP traps configuration					
Parameter	Description				
Enable SNMP traps	Enable/disable SNMP traps sending.				
Source IP address	ce IP Set the IP address of the device which sends traps.				

To create a new record, click the "Add SNMP Trap" button.



Figure - Create SNMP trap

In the new window select the traps type to send and fill in the following parameters:

Parameter	Description	
Destination address	Set the monitoring system server IP address.	
Port	Set the monitoring system UDP port.	