


_InfiLINK Evolution / InfiMAN Evolution Numbering convention

InfiLINK Evolution / InfiMAN Evolution part number has the following structure



Structure items are described below

Item	Description
1	Product family name: E - InfiLINK Evolution / InfiMAN Evolution.
2	Frequency range: 5 - device in the range of 5 GHz. 6 - base station sector in the range of 6 GHz . - subscriber terminal in the ranges of 5 and 6 GHz.
3	- BS - base station sector. - ST - subscriber terminal or PTP device.
4	Antenna gain. Base Station Sectors: - I - integrated antenna with 16 dBi gain; - Q - integrated antenna with 21 dBi gain; - E - devices for an external antenna connection. Subscriber Terminals and PTP devices: 18 - integrated antenna with 18 dBi gain; 23 - integrated antenna with 23 dBi gain; 25 - integrated antenna with 25 dBi gain; 28 - integrated antenna with 28 dBi gain; - E - devices for an external antenna connection.
5	Additional options: - t - extended temperature range: -55 ... +60 °C. - c - subscriber terminal for PtMP topology (cannot be a "master"). - d - device modified for InfiDRIVE system. - L - Base Btation Sectors lite version with limited functionality: - Throughput: up to 360 Mbps. - Channel width: 20, 40 MHz. - Maximum number of simultaneous subscribers supported: 10.