


## \_InfiLINK Evolution / InfiMAN Evolution Numbering convention

InfiLINK Evolution / InfiMAN Evolution part number has the following structure



Structure items are described below

Item	Description
1	Product family name: <ul style="list-style-type: none"> <li>E - InfiLINK Evolution / InfiMAN Evolution.</li> </ul>
2	Frequency range: <ul style="list-style-type: none"> <li>5 - device in the range of 5 GHz.</li> <li>6 <ul style="list-style-type: none"> <li>base station sector in the range of 6 GHz .</li> <li>subscriber terminal in the ranges of 5 and 6 GHz.</li> </ul> </li> </ul>
3	<ul style="list-style-type: none"> <li>BS - base station sector.</li> <li>ST - subscriber terminal or PTP device.</li> </ul>
4	Antenna gain. <p>Base Station Sectors:</p> <ul style="list-style-type: none"> <li>I - integrated antenna with 16 dBi gain;</li> <li>Q - integrated antenna with 21 dBi gain;</li> <li>E - devices for an external antenna connection.</li> </ul> <p>Subscriber Terminals and PTP devices:</p> <ul style="list-style-type: none"> <li>18 - integrated antenna with 18 dBi gain;</li> <li>23 - integrated antenna with 23 dBi gain;</li> <li>25 - integrated antenna with 25 dBi gain;</li> <li>28 - integrated antenna with 28 dBi gain;</li> <li>E - devices for an external antenna connection.</li> </ul>
5	Additional options: <ul style="list-style-type: none"> <li>t - extended temperature range: -55 ... +60 °C.</li> <li>c - subscriber terminal for PtMP topology (cannot be a "master").</li> <li>d - device modified for InfiDRIVE system.</li> <li>L - Base Btation Sectors lite version with limited functionality: <ul style="list-style-type: none"> <li>Throughput: up to 360 Mbps.</li> <li>Channel width: 20, 40 MHz.</li> <li>Maximum number of simultaneous subscribers supported: 10.</li> </ul> </li> </ul>