

## Command Line menu



Successfully pass the free certification exam at IW Academy and become an Infinet Certified Engineer.

[To the certification exam](#)

The "Command Line" page emulates CLI (command line interface) in the Web interface. This allows managing and monitoring the device by using all the commands and functions that are available via standard CLI.

In order to run one or a set of **WANFlex** commands, type them in the command field and then click the «**Execute**» button. The output of the commands is displayed in the section above the command field:

```
mint prf0 -name "BSE"
mint prf0 -nodeid 37426
mint prf0 -type master
mint prf0 -mode fixed
mint prf0 -nolog
mint prf0 -authmode public
mint prf0 -airupdate disable
mint prf0 -rcmdserver enabled
mint prf0 start

#Switch virtual Interface config
svi 1 group 1

#SNMP configuration
snmpd user admin add security authNoPriv pass "masterkey" \
    access readWrite class admin
snmpd vldisable
snmpd start

#WEB configurator
webcfg start

#Add-on devices control
ctl heater -s nolog

#LLDP parameters
lldp eth0 enable txrx
lldp eth1 enable txrx
```

System Info

System Config

System Log

License Info

Reset All Counters

Routing Table

Switch Statistics

IGMP Statistics

Interface Table

Radio Statistics

Link Status

Radio Scanner

Traffic Monitor

Command:

Execute

Clear All Fields

**Figure - Command line**

In the "Command Line" menu, the commands are only executed, but not saved into the configuration. To execute the command and save it in the device configuration, use the "config save" command.



### CAUTION

After changing the configuration in the web interface, the commands that were previously applied through the CLI and are missing in the web interface will be lost. To add these commands use the "Basic settings" - "Additional commands" section.